

Einfassprofile für Lochbleche





Ihr Vorteil: Alle Positionen ständig vorrätig! Stangenlänge generell 3000 mm.

Bezeichnung	Schlitzweite	Wandstärke	Material	Gewicht
ProMetall	(mm)	(mm)		(kg/lfm)
R 18 - 1,7	1,70	1,25	St37-2	0,46
E 20 x 20 - 1,7	1,70	1,25	St37-2	0,53
R 27 - 1,7	1,70	1,50	St37-2	1,15
E 20 x 30 - 1,7	1,70	1,50	St37-2	1,27

R 18 - 1,7	1,70	1,25	SVZ	0,46
E 20 x 20 - 1,7	1,70	1,25	SVZ	0,53
R 27 - 1,7	1,70	1,50	SVZ	1,15
E 20 x 30 - 1,7	1,70	1,50	SVZ	1,27

R 18 - 1,7	1,70	1,25	Al 99,5	0,16
E 20 x 20 - 1,7	1,70	1,25	Al 99,5	0,19
R 27 - 1,7	1,70	1,50	Al 99,5	0,45
E 20 x 30 - 1,7	1,70	1,50	Al 99,5	0,45

R 18 - 1,7	1,70	1,25	1.4301	0,46
R 18 - 1,7	1,70	1,25	1.4301 geschl.	0,46
E 20 x 20 - 1,7	1,70	1,25	1.4301	0,53
R 27 - 1,7	1,70	1,50	1.4301	1,15
R 27 - 1,7	1,70	1,50	1.4301 geschl.	1,15
E 20 x 30 - 1,7	1,70	1,50	1.4301	1,27
E 20 x 30 - 1,7	1,70	1,50	1.4301 geschl.	1,27



Einfassprofile für Kripp-/Wellgitter und Streckmetall

WG 30 x 30	5,7	1,5	St37-2	1,48
WG 40 x 40	7,5	2	St37-2	2,47

